


Discontinued  
The model has been discontinued.



Specification

|                                         |                     |
|-----------------------------------------|---------------------|
| Sensor                                  |                     |
| Sensor type                             | CMOS Color          |
| Shutter                                 | Global Shutter      |
| Sensor characteristic                   | Linear              |
| Pixel Class                             | 3 MP                |
| Resolution                              | 3.15 Mpix           |
| Resolution (h x v)                      | 2048 x 1536 Pixel   |
| Aspect ratio                            | 4:3                 |
| ADC                                     | 12 bit              |
| Color depth (camera)                    | 8 bit               |
| Optical sensor class                    | 1/1.8"              |
| Optical Size                            | 7.066 mm x 5.300 mm |
| Optical sensor diagonal                 | 8.83 mm 1/1.8"      |
| Pixel size                              | 3.45 µm             |
| CRA (Chief Ray Angle)                   | 0 °                 |
| Manufacturer                            | Sony                |
| Sensor Model                            | IMX265LQR-C         |
| Gain (master/RGB)                       | 24x/4x              |
| AOI horizontal                          | -                   |
| AOI vertical                            | -                   |
| AOI image width / step width            | - / -               |
| AOI image height / step width           | - / -               |
| AOI position grid (horizontal/vertical) | - / -               |
| Binning horizontal                      | -                   |
| Binning vertical                        | -                   |
| Binning method                          | -                   |
| Binning factor                          | -                   |
| Decimation (subsampling) horizontal     | -                   |
| Decimation (subsampling) vertical       | -                   |
| Decimation (subsampling) method         | -                   |



Model

|                                   |                    |
|-----------------------------------|--------------------|
| Frame rate freerun mode           | 20 fps             |
| Frame rate trigger (continuous)   | 22 fps             |
| Frame rate trigger (maximum)      | 22 fps             |
| Exposure time (minimum - maximum) | 0.042 ms - 2000 ms |
| Power consumption                 | 6 W - 11 W         |
| Image memory                      | 128 MB             |

Ambient conditions

The temperature values given below refer to the outer device temperature of the camera housing.


|                                             |                                 |
|---------------------------------------------|---------------------------------|
| Allowed device temperature during operation | 0 °C - 55 °C / 32 °F - 131 °F   |
| Allowed ambient temperature during storage  | -20 °C - 60 °C / -4 °F - 140 °F |
| Humidity (relative, non-condensing)         | 0 % - 80 %                      |

Connectors

|                     |                                          |
|---------------------|------------------------------------------|
| Interface connector | GigE M12, screwable                      |
| I/O connector       | 12-pin M12 connector (Attend 216A-12MSR) |
| Power supply        | 12 V - 24 V or PoE                       |

Pin assignment I/O connector

|    |                                                                 |
|----|-----------------------------------------------------------------|
| 1  | Power supply 12-24 V DC (VBUS)                                  |
| 2  | Reference level (ground) for power supply and RS-232 (VBUS GND) |
| 3  | Trigger input with optocoupler (Opto IN 0)                      |
| 4  | Input 1 with optocoupler (Opto IN 1)                            |
| 5  | Common reference level for all Opto IN (Opto IN COM)            |
| 6  | Common reference level for all Opto OUT (Opto OUT COM)          |
| 7  | Output 1 with optocoupler (Opto OUT 1)                          |
| 8  | Output 2 with optocoupler (Opto OUT 2)                          |
| 9  | Serial interface (RS232 Rx/D)                                   |
| 10 | Serial interface (RS232 Tx/D)                                   |
| 11 | Input 2 with optocoupler (Opto IN 2)                            |
| 12 | Flash output with optocoupler (Opto OUT 0)                      |



Design

|                  |                             |
|------------------|-----------------------------|
| Lens Mount       | C-Mount                     |
| IP code          | IP65, IP67                  |
| Dimensions H/W/L | 41.0 mm x 53.0 mm x 75.0 mm |
| Mass             | 282 g                       |
| Housing material | Aluminum                    |

Features

List of on-camera image pre-processing features.

All features of the table are available via our IDS peak software for image pre-processing on the host computer (sensor model dependent).

|                   |                             |   |
|-------------------|-----------------------------|---|
| Image Acquisition | Freerun                     | ✓ |
|                   | Software trigger            | ✓ |
|                   | Hardware trigger            | - |
|                   | Trigger controlled exposure | - |
|                   | Denoiser                    | - |
|                   | Long exposure               | - |
|                   | Line scan                   | - |

## IDS NXT rome Rev.1.2 GS18031C-HQ (1009159)

|                           |                                |             |
|---------------------------|--------------------------------|-------------|
| Flashing                  | Flashing                       | ✓           |
|                           | PWM flashing                   | -           |
| Image Adjustments         | Auto exposure                  | -           |
|                           | Auto gain                      | ✓           |
|                           | Auto whitebalance              | ✓           |
|                           | Color correction               | -           |
|                           | Gamma                          | ✓           |
|                           | LUT                            | -           |
|                           | Mirror/flip                    | X/Y         |
| On-board Image Processing | Pixel formats                  |             |
|                           | Region of interest             | -           |
|                           | Decimation (FPGA)              | -           |
|                           | Decimation (Sensor)            | (2,4)x(2,4) |
|                           | Binning (FPGA)                 | ✓           |
| Others                    | Chunks                         | -           |
|                           | Sequencer                      | -           |
|                           | Firmware update                | -           |
|                           | 1st supported firmware version | 3.0         |