# GV-5240FA-C-HQ Rev.1.2 (AB12429)

**In series**
The model is in series and available for the long term.






## Specification

### Sensor

| | |
|---|---|
| Sensor type | CMOS Color |
| Shutter | Global Shutter |
| Sensor characteristic | Linear |
| Pixel Class | 1.3 MP |
| Resolution | 1.31 Mpix |
| Resolution (h x v) | 1280 x 1024 Pixel |
| Aspect ratio | 5:4 |
| ADC | 10 bit |
| Color depth (camera) | 10 bit |
| Optical sensor class | 1/1.8" |
| Optical Size | 6.784 mm x 5.427 mm |
| Optical sensor diagonal | 8.69 mm 1/1.8" |
| Pixel size | 5.3 µm |
| CRA (Chief Ray Angle) | 12 ° |
| Manufacturer | e2v |
| Sensor Model | EV76C560ACT |
| Gain (master/RGB) | 16x/4x |
| AOI horizontal | same frame rate |
| AOI vertical | increased frame rate |
| AOI image width / step width | 256 / 2 |
| AOI image height / step width | 2 / 2 |
| AOI position grid (horizontal/vertical) | 2 / 2 |
| Binning horizontal | same frame rate |
| Binning vertical | same frame rate |
| Binning method | Horizontal: addition / Vertical: addition |
| Binning factor | 2x2 |
| Decimation (subsampling) horizontal | - |
| Decimation (subsampling) vertical | - |
| Decimation (subsampling) method | M/C automatic |







IDS Imaging Development Systems Inc.
800 W Cummings Park Ste 2950 · Woburn, MA 01801-7221 · Phone +1 (781) 787-0048 · E-Mail usasales@ids-imaging.com

## Model

| | |
|---|---|
| Frame rate freerun mode | 59 fps |
| Frame rate trigger (continuous) | 60 fps |
| Frame rate trigger (maximum) | 60 fps |
| Exposure time (minimum - maximum) | 0.009 ms - 169 ms |
| Power consumption | 1.7 W - 2.2 W |
| Image memory | 128 MB |

## Ambient conditions

The temperature values given below refer to the outer device temperature of the camera housing.


| | |
|---|---|
| Allowed device temperature during operation | -20 °C - 55 °C / -4 °F - 131 °F |
| Allowed ambient temperature during storage | -20 °C - 60 °C / -4 °F - 140 °F |
| Humidity (relative, non-condensing) | 0 % - 100 % |

## Connectors

| | |
|---|---|
| Interface connector | GigE M12, screwable |
| I/O connector | 8-pin Binder connector (Binder series 712: 09-0427-020-08) |
| Power supply | 12 V - 24 V or PoE |

## Pin assignment I/O connector

| | |
|---|---|
| 1 | Trigger input with optocoupler (+) - Line 0 |
| 2 | Input power supply (VCC) 12-24 V DC |
| 3 | General Purpose I/O (GPIO) 1 - Line 2 |
| 4 | Ground (GND) |
| 5 | Flash output with optocoupler (+) - Line 1 |
| 6 | Flash output with optocoupler (-) - Line 1 |
| 7 | Trigger input with optocoupler (-) - Line 0 |
| 8 | General Purpose I/O (GPIO) 2 |




## Design

| | |
|---|---|
| Lens Mount | C-Mount |
| IP code | IP66, IP67, IP69, IPx9K |
| Dimensions H/W/L | 41.0 mm x 53.0 mm x 42.7 mm |
| Mass | 173 g |
| Housing material | Aluminum |

## Features

List of on-camera image pre-processing features.
All features of the table are available via our IDS peak software for image pre-processing on the host computer (sensor model dependent).

| | | |
|---|---|---|
| Image Acquisition | Freerun | ✓ |
| | Software trigger | ✓ |
| | Hardware trigger | ✓ |
| | Trigger controlled exposure | - |
| | Denoiser | ✓ |
| | Long exposure | - |
| | Line scan | - |
| Flashing | Flashing | ✓ |
| | PWM flashing | ✓ |


IDS Imaging Development Systems Inc.
800 W Cummings Park Ste 2950 · Woburn, MA 01801-7221 · Phone +1 (781) 787-0048 · E-Mail usasales@ids-imaging.com

| | | |
|---|---|---|
| Image Adjustments | Auto exposure | ✓ |
| | Auto gain | ✓ |
| | Auto whitebalance | ✓ |
| | Color correction | ✓ |
| | Gamma | ✓ |
| | LUT | ✓ |
| | Mirror/flip | - |
| On-board Image Processing | Pixel formats | Mono8<br>BayerRG8<br>BayerRG10<br>BayerRG10p<br>BayerRG12<br>BayerRG12p<br>BGR8<br>RGB8<br>BGR10p32<br>RGB10p32 |
| | Region of interest | ✓ |
| | Decimation (FPGA) | ✓ |
| | Decimation (Sensor) | |
| | Binning (FPGA) | ✓ |
| | Binning (Sensor) | 2x2<br>Increases frame rate. |
| Others | IP settings | ✓ |
| | Bandwidth management | ✓ |
| | Chunks | - |
| | Sequencer | - |
| | PTP | ✓ |
| | Firmware update | ✓ |
| | 1st supported firmware version | 2.10 |



IDS Imaging Development Systems Inc.
800 W Cummings Park Ste 2950 · Woburn, MA 01801-7221 · Phone +1 (781) 787-0048 · E-Mail usasales@ids-imaging.com